

D156

Super-slim design, multi-touch



FEATURE

- 15.6"IPS LCD 1920*1080 pixels
- 5 points capacitive touch
- Super slim design
- Aluminium alloy frame
- Wide view angle
- HDMI & USB (touch) port

SPECIFICATIONS

Display	Size	15.6 inch	
	Resolution	1920×1080	
	Viewing Angle	85°,vertical / horizontal	
	Brightness	350nits(typ)	
	Display Color	16.7M	
	Contrast Ratio	1200 : 1	
	Response Time	30 ms(Typ)	
	Backlight Life(hours)	20,000 hrs(min)	
Touch Screen	Touchscreen Type	Multi-touch capacitive	
	Surface Hardness	6H	
Environment	Operating Temperature	-10~+55°C	
	Storage Temperature	-20~+60°C	
	Operating Humidity	0%~95% (Non Condensing)	
	Front Panel Protection	IP54	
I/O	DC Jack	12V DC input	
	HDMI	Type-A,With Brightness Control	
	USB-B	Type-B, Touch panel	
	DB9	RS485	
Power	Input Voltage	12V	
Compliance	Regional Certification	CCC /CE / VCCI	
Packing	Box Dimension	475 × 295 × 96mm	
	Net Weight	1.66KG	
	Gross Weight	2.1KG, with box and adaptor	
	Packing List		1 x HDMI Cable
			1xUSB(Type-A to type-B)Cable, 2 meters
		8 x Screws, for VESA or RAM Mount	
		Adaptor, AC100~240V, 24W, 12V/2A, With PSE(Japan) / CCC(CN)	
		Adaptor, AC100~240V, 24W, 12V/2A, With CE(EU)	

ORDER INFORMATION

PartNumber	Description
D156NS001	D156, 15.6"1920×1280 Industrial Display
PXDCAB002	HDMI Cable, 2 meters
PXDCAB010	HDMI Cable, 3.5meters
PXDCAB003	USB(Type-A to type-B)Cable, 2 meters
PXDCAB011	USB(Type-A to type-B)Cable, 3.5 meters
XXDARM001	Desk ARM, support VSEA 75 × 75mm and RAM

DIMENSIONS

